

## TECHNICAL DATA SHEET **CALCE LUCIDA**

Calce Lucida is a material composed of selected fragments of marble dust, seasoned lime and refined additives which allow for easy application with substrate adhesion. Thanks to its characteristic mineral composition, this product has a good resistance to moisture and mold and has excellent breathability, while maintaining good impermeability. This finish is extremely glossy and smooth to the touch, semi-transparent in appearance with the peculiarity of allowing a glimpse of the colors and the different working hands underneath.



### TECHNICAL DATA

- **Specific weight:** 1500 kg / l approx.
- **Particle size:** less than 10 micron
- **Consumption:** 0.3 kg / sqm per coat (varies according to thickness applied).



### USAGE

Is used as a protective coating and prestigious finish for new and old surfaces. This product can be used on any type of surface after adequate preparation of the base layer.



### SURFACE PREPARATION

The surface to be coated must be dry, free from dust and dirt and clean of any traces of non-adherent, oil, grease or other deposits. Before proceeding with the preparation coat, wait at least 28 days after any plaster has been applied. With highly absorbent plaster or when using porous surfaces, the application of an insulating primer or fixative is also recommended. In the presence of non-absorbent smooth surfaces proceed by applying FONDO FINO. To achieve a perfect decorative degree it is advisable to apply one more coat of lime product worked as desired, in color or not with the finish, depending on the effect to be recreated.



### APPLICATION

The product is ready to use. Apply a first layer of material with stainless steel trowel on the previously worked surface, making sure to distribute it uniformly, do not smudge, line or overlaps. It can be finished with a second coat, variable according to the desired finish, with a smaller quantity of material. When the finish is almost dry, proceed to crush the surface with a stainless steel trowel, making more and more pressure. This phase is very important for compacting the product that the more is worked the more is able to scan the layers applied.



### CAUTIONS AND SUPPLY

- Apply only on plasters seasoned and dry. Apply at a temperatures higher than +5 °C and lower than +35 °C.
- Colours: available white. On request tone color chart or with reference to the sample.



### PACKAGING

CALCE LUCIDA is available as a ready-to-use paste, in 2.5 kg, 5 kg, 10 kg and 20 kg containers.



### STORAGE

Protect from frost. Store at temperatures of above 5 and below 35 degrees Celsius. The paint has a shelf life of two years if stored correctly. The stability of ready opened or modified tins cannot be guaranteed under any circumstance. We always recommend a preliminary test.

*The reported data refer to laboratory tests; in practical construction applications, they may vary significantly depending on the application conditions. The user is responsible for verifying their suitability.*